

403055 STANDARD SEALS_CLASS 150



TWO-way ball valve, Flat Body

Drive: ISO 5211 flange for actuator

Connection: Threaded holes for EN 1759-1 CLASS 150 (exANSI 150)

Flow: Full

Material: Aisi 316L (1.4404)

Measure: from DN15 to DN100

Seals: Modified Virgin P.T.F.E.

Operating temperature: -20°C+170°C

* MOUNTING KIT NEEDED Art. 747540

On request:

Antistatic device ATEX:

II 2G Ex h IIC T4 Gb

II 2D Ex h IIIC T135°C Db

M.O.C.A. CE 1935/2004

• Seals made of:

PTFE with glass -20°C+170°C

PTFE with carbographite -20°C+180°C

PTFE with inox -20°C+200°C

UHMW High-molecular weight polyethylene -20°C+80°C

EN 1759-1 CLASS 150 (exANSI 150)	DN	L	C	H	D	I	R	A	n° x M	Kg	ISO-DIN	d	o	□	e	f	Nm	COD. AISI 316L
1/2"	15	35		32,5	90	1,5	35	60,6	4xM12	-	F.03	10		9	36	M.5	8	403055 61410
3/4"	20	38		40	100	1,5	43	69,8	4xM12	-	F.04	11		11	42	M.5	12	403055 62010
1"	25	42		42,5	105	2	51	79,4	4xM12	-	F.04	11		11	42	M.5	15	403055 62610
1*1/4	32	54		57,5	130	2	63,5	88,9	4xM12	-	F.05	16		14	50	M.6	18	403055 63010
1*1/2	40	66		62	140	3	73	98,4	4xM12	-	F.05	16		14	50	M.6	25	403055 63410
2"	50	82		70	150	3	92	120,6	4xM16	-	F.05	16		14	50	M.6	30	403055 63810
2*1/2	65	95		80,5	180	3	119	139,7	4xM16	-	F.07	18		17	70	M.8	45	403055 64410
3"	80	118		92	200	3	127	152,4	4xM16	-	F.07	18		17	70	M.8	85	403055 64810
4"	100	140		101	220	3	157	190,5	8xM16	-	F.10			17	102	M.10	90	403055 65410

* MOUNTING KIT NEEDED Art. 747540 or LEVER Art. 9354112

