

283004_L_HIGH PRESSURE PN250



THREE-way ball valve ATEX II 2 G-D T4 with "L" port

Drive: ISO 5211 - DIN 3337 flange for actuator

Connection: NPT female/female/female thread

Flow: Full

Material: Aisi 316L (1.4404)

Measure: from 1/4" to 1"

Seals: **INOX filled PTFE**

Operating temperature: -20°C+200°C


Outer finish: Turned

Screws for mounting actuator included


On request:

M.O.C.A. CE 1935/2004

•MANUAL with LEVER



G (NPT)	DN	L	I	P	H	M	N	ØA	PN	Kg	ISO-DIN	Ø a	b	Øc x o	□	d	e	f	g	n° 4 BOLTS	Nm	CODE
1/4" -	8	70	15	13	84	53	31	60	250	1.35	F.03 / F.04	55	10	25x6	9/11	9.5	36	42	6	M5x16	20	283004A60450
3/8"	8	70	15	13	84	53	31	60	250	1.30	F.03 / F.04	55	10	25x6	9/11	9.5	36	42	6	M5x16	20	283004A60850
1/2"	12	80	18	15	87	54	33	65	250	1.65	F.04 / F.05	65	10	30x6	11/14	10.5	42	50	6	M5x16/M6x16	25	283004A61450
3/4"	17	90	19	15	94	56.5	37.5	75	250	2.22	F.04 / F.05	65	10	30x6	11/14	10.5	42	50	6	M5x16/M6x16	35	283004A62050
1"	22	100	20	16	100	59.5	40.5	85	250	2.90	F.04 / F.05	65	10	30x6	11/14	10.5	42	50	6	M5x16/M6x16	40	283004A62650



POS.	DENOMINATION	PCS	MAT.
1	Corpo.	1	AISI 316L
2	Sleeve	2	AISI 316L
3	Ball	1	AISI 316L
4	Stem	1	AISI 316L
5	Plug	1	AISI 316L
6	Pin Seals	1	GLASS filled PTFE
7	Pin Seals	1	INOX FILLED PTFE
8	Pin Seals	1	INOX FILLED PTFE
9	Seal	3	INOX FILLED PTFE
10	Ball Seals	2	INOX FILLED PTFE
11	O-Ring Pin	2	FKM
12	O-Ring Sleeve	3	FKM
13	Seeger	1	AISI 420

