




## MONO TYPE S61 - GEARBOX OPERATED



# MONO TYPE S61 - GEARBOX OPERATED DN50 - DN200





Size DN 50 to DN 200, Design EN593  
Face to face acc. EN558.1 series 16  
Flange connections: DIN PN6-10-16-25  
ANSI B 16.5 Cl. 150#, JIS B 2211 5K, 10K  
Temperature -40/+250°C  
Various pressure ratings up to 25 bar  
Top flange according ISO 5211  
Vacuum to 1\*10<sup>-3</sup> 0.2 Torr absolute

## Standard available materials :

| BODY        | DISC        | SHAFT     | SEAT                    |
|-------------|-------------|-----------|-------------------------|
| EN-JS1030   | BS 1400 AB2 | SS 1.4122 | NBR -15°C / +80°C       |
| A216 WCB    | EN-JS1030   | SS 431    | EPDM -23°C / +120°C     |
| SS 1.4408   | SS 1.4408   | SS 1.4462 | Viton -0°C / +200°C     |
| BS 1400 AB2 | SD 2507     | SD F53    | Silicone -40°C / +230°C |

| Size   | Gearbox   | A   | B   | C   | D  | E      | F  | G    | H   | K  | L   | O   | Weight ± Kg |
|--------|-----------|-----|-----|-----|----|--------|----|------|-----|----|-----|-----|-------------|
| DN 50  | ALFA - 12 | 52  | 65  | 118 | 43 | SP-100 | 50 | 36.5 | 114 | 5  | 27  | 165 | 6.6         |
| DN 65  | ALFA - 12 | 63  | 78  | 126 | 46 | SP-100 | 50 | 36.5 | 114 | 9  | 43  | 185 | 7.4         |
| DN 80  | ALFA - 12 | 78  | 97  | 133 | 46 | SP-100 | 50 | 36.5 | 114 | 16 | 62  | 200 | 8.2         |
| DN 100 | ALFA - 12 | 103 | 98  | 147 | 52 | SP-100 | 50 | 36.5 | 114 | 26 | 90  | 220 | 9.7         |
| DN 125 | ALFA - 12 | 125 | 110 | 160 | 56 | SP-100 | 50 | 36.5 | 114 | 34 | 110 | 250 | 12.0        |
| DN 150 | ALFA - 12 | 155 | 133 | 180 | 56 | SP-100 | 50 | 36.5 | 114 | 50 | 145 | 285 | 14.5        |
| DN 200 | ALFA - 25 | 201 | 168 | 204 | 60 | SC-150 | 62 | 44.6 | 151 | 71 | 193 | 340 | 19.5        |


# MONO TYPE S61 - GEARBOX OPERATED DN250 - DN600



Size DN 250 to DN600, Design EN593  
Face to face acc. EN558.1 series 16  
Flange connections: DIN PN6-10-16-25  
ANSI B 16.5 Cl. 150#, JIS B 2211 5K, 10K  
Temperature -40/+250°C  
Various pressure ratings up to 25 bar  
Top flange according ISO 5211  
Vacuum to 1\*10<sup>-3</sup> 0.2 Torr absolute

## Standard available materials :

| BODY        | DISC        | SHAFT     | SEAT                    |
|-------------|-------------|-----------|-------------------------|
| EN-JS1030   | BS 1400 AB2 | SS 1.4122 | NBR -15°C / +80°C       |
| A216 WCB    | EN-JS1030   | SS 431    | EPDM -23°C / +120°C     |
| SS 1.4408   | SS 1.4408   | SS 1.4462 | Viton -0°C / +200°C     |
| BS 1400 AB2 | SD 2507     | SD F53    | Silicone -40°C / +230°C |



| Size   | GEARBOX    | A   | B   | C   | D   | E      | F   | G     | H   | K   | L   | O   | Weight ± Kg |
|--------|------------|-----|-----|-----|-----|--------|-----|-------|-----|-----|-----|-----|-------------|
| DN 250 | ALFA - 55  | 249 | 204 | 245 | 68  | SW-250 | 73  | 55    | 235 | 91  | 241 | 420 | 32.2        |
| DN 300 | ALFA - 55  | 302 | 239 | 270 | 78  | SW-250 | 73  | 55    | 235 | 112 | 291 | 455 | 44.1        |
| DN 350 | ALFA - 100 | 340 | 295 | 315 | 78  | SW-300 | 95  | 71    | 272 | 128 | 324 | 515 | 74.7        |
| DN 400 | ALFA - 100 | 397 | 320 | 350 | 102 | SW-300 | 95  | 71    | 272 | 144 | 376 | 580 | 94.7        |
| DN 450 | ALFA - 200 | 438 | 353 | 375 | 114 | SW-400 | 102 | 86    | 310 | 163 | 426 | 635 | 134.1       |
| DN 500 | ALFA - 200 | 489 | 387 | 415 | 127 | SW-400 | 102 | 86    | 310 | 182 | 475 | 715 | 168.1       |
| DN 600 | ALFA - 350 | 590 | 453 | 562 | 154 | SW-500 | 106 | 104.5 | 336 | 219 | 572 | 835 | 263.8       |